


Designed for installation as the top layer in two layer roofing system on buildings and constructions, for waterproofing of engineering structures. Can be used on new construction or repair. Not recommended to use as single ply waterproofing.



Torch-on application to the prepared surface.

TECHNICAL DATA

PRODUCT	FLOW RESISTANCE, °C	MAXIMUM TENSILE FORCE L/T, N/50 mm	RESISTANCE TO TEARING, N	ELONGATION, %	REINFORCEMENT TYPE / WEIGHT
BIPOL EKP	≥85	600±200 500±200	180±50 180±50	50±25 50±25	polyester, 160 g/m ²
BIPOL STANDART EKP	≥85	600±200 500±200	180±50 180±50	50±25 50±25	polyester, 160 g/m ²
BIPOL XL EKP	≥85	600±200 500±200	180±50 180±50	50±25 50±25	polyester, 160 g/m ²

LOGISTIC DATA

PRODUCT	WEIGHT, kg/m ²	THICKNESS, mm	LENGTH, m	WIDTH, m	ROLLS PER PALLET
BIPOL EKP	4.0-0.200	-	10	1	25
BIPOL STANDART EKP	4.5-0.225	-	10	1	23
BIPOL XL EKP	5.0-0.250	-	10	1	20

AVAILABLE COLOURS

