


UNIFLEKS EKP

-20°C



Designed for installation as the top layer in two layer roofing system on buildings and constructions, for waterproofing of engineering structures. Can be used on new construction or repair. Not recommended to use as single ply waterproofing.



Torch-on application to the prepared surface.

TECHNICAL DATA

PRODUCT	FLOW RESISTANCE, °C	MAXIMUM TENSILE FORCE L/T, N/50 mm	RESISTANCE TO TEARING, N	ELONGATION, %	REINFORCEMENT TYPE / WEIGHT
UNIFLEKS EKP	≥95	700±100 500±100	180±30 180±30	50 ±25 50 ±25	polyester, 160 g/m ²
UNIFLEKS EKP 5.0	≥95	700±100 500±100	180±30 180±30	50 ±25 50 ±25	polyester, 180 g/m ²
UNIFLEKS EKP EXTRA	≥95	700±100 500±100	180±30 180±30	50 ±25 50 ±25	polyester, 180 g/m ²

LOGISTIC DATA

PRODUCT	WEIGHT, kg/m ²	THICKNESS, mm	LENGTH, m	WIDTH, m	ROLLS PER PALLET
UNIFLEKS EKP	4.7-0.235	3.8±0.1	10	1	23
UNIFLEKS EKP 5.0	5.0-0.250	4.1±0.1	10	1	20
UNIFLEKS EKP EXTRA	5.5-0.275	4.4±0.1	8	1	23

AVAILABLE COLOURS

