

# WINTECHNO MAT

Item Code: SEE DN

Issue date: 21.05.13<sup>th</sup>

Review # 04

Page 1 of 2

## DESCRIPTION

Non-woven, polyester reinforcement mat for WINKLER range's liquid waterproofing membranes. The product has the following features:

- Non-allergenic
- Rot-proof
- Resistant to atmospheric agents
- Easy-fitting to every kind of surface

## USES

WINTECHNO MAT is an ideal reinforcement for liquid waterproofs. Thanks to its flexibility it assures a great adaptation to the treated surfaces while for its extreme permeability it goes together well with the waterproofing liquid. Its versatility and the small thickness make WINTECHNO MAT an effective instrument even in case of existing floors, where fallowing height differences, particularly near doorsteps, is extremely binding.

WINTECHNO MAT is a valid system to be used on large surfaces (>50sqm), tiled floors, gutters and on substrates subject to movements, to allow the liquid waterproofer to effectively absorb the tensions created by the substrate.

## APPLICATION

For the application, always refer to the technical data sheets of the liquid membrane chosen for waterproofing.

			WINTECHNO MAT	
				U.M
Weight		ISO 9073 - 1	70	g/m²
Thickness		ISO 9073 - 1	0.65	mm
Breaking load	L T	EN 12311 - 1	450 170	N/5 cm
Breaking elongation	L T	EN 12311 - 1	16 30	%

## TECHNICAL SHEET

#### **SUPPLY DATA**

	WIN TECHNO MAT	
		U.M.
Height	100	cm
Lenght	100	m
Development	100	m²
Quantity per pallet	20	rolls
	2,000	m²

# **TECHNICAL SHEET**



# **SAFETY INSTRUCTIONS**

### PRECAUTIONS

For information about safety, user must refer to the most recent Safety Data Sheet, edited in accordance with the regulations in force, which contains physical, toxic and other data about the product in use.

## ECOLOGY

Do not through out the product and/or empty containers in the environment. Consult the most recent Safety Data Sheet for further information about disposals.

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline If at all in doubt, preliminary tests should be carried out. WINKLER S.r.I. reserves the right to modify and update said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.

Winkler Srl

Via M. Buonarroti, 15 - 20093 Cologno Monzese (Mi) - Italy | Tel. +39 02 26 700 605 - Fax +39 02 26 700 621 info@winklerchimica.com - www.winklerchimica.com

